


REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
4.	WAS A CUSTOM TOOL	08/29/11	JH



SECTION A - A

Ao = 11.40
Bo = 13.40
Ko = 2.00

NOTES:

1. 10 SPROCKET HOLE PITCH CUMULATIVE TOLERANCE ± 0.2
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
3. Ao AND Bo ARE CALCULATED ON A PLANE AT A DISTANCE "R" ABOVE THE BOTTOM OF THE POCKET.



ADVANTEK[®]
engineered confidence™

TITLE ADVANTEK PART DRAWING NUMBER BG1113-A CARRIER TAPE			
TOLERANCES - UNLESS NOTED 1PL ± 0.2 2PL ± 0.10	MATERIAL PS+C	DWG SIZE B	
ALL DIMS IN MILLIMETERS PER ASME Y14.5M			
DRAWN BY RJB/BVB	DATE 4/14/99	SCALE 3:1	SHEET 1 OF 1
CK'D BY	PROJECT NO. T-8497-A / 7667.00	DWG NO. T102199AT	REV 4