


REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
2	WAS CLOSED TOOL	3/7/11	BTH
3	RESTORED ORIGINAL WIDTH TOLERANCE	3/1/12	BTH



SECTION A - A

Ao = 6.90
Bo = 9.60
Ko = 3.40

- NOTES:
1. 10 SPROCKET HOLE PITCH CUMULATIVE TOLERANCE ± 0.2
 2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
 3. Ao AND Bo ARE CALCULATED ON A PLANE AT A DISTANCE "R" ABOVE THE BOTTOM OF THE POCKET.



TITLE ADVANTEK PART DRAWING NUMBER SMD-16-A CARRIER TAPE			
TOLERANCES - UNLESS NOTED 1PL ± 0.2 2PL ± 0.10	MATERIAL PS+C	DWG SIZE B	
ALL DIMS IN MILLIMETERS PER ASME Y14.5M			
DRAWN BY SDC	DATE 3/27/1995	SCALE 3:1	SHEET 1 OF 1
CK'D BY	PROJECT NO. A0327-95-1	DWG NO. A0327-95-1	REV 3